



High-end Power Semiconductor Manufacturer

ZK400A 1100-2000V Fast Recovery Diode

- Low switching losses
- Low reverse recovery charge High
- power cycling capability



Average forward current				I_{FAV}	390 A	
Repetitive peak reverse voltage				V_{RRM}	1100 – 2000 V	
Reverse recovery time				t_{rr}	2.00 μ s	
V_{RRM} , V	1100	1200	1400	1600	1800	2000
Voltage code	11	12	14	16	18	20
T_j , °C	– 60 – 150					


MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions	
ON-STATE					
I_{FAV}	Average forward current	A	390	$T_c=85\text{ }^{\circ}\text{C}$; Double side cooled; 180° half-sine wave; 50 Hz	
I_{FSM}	Surge forward current	kA	5.4	$T_j=T_{j\text{ max}}$	180° half-sine wave; $t_p=10\text{ ms}$; $V_R=0.6V_{\text{RRM}}$
I^2t	Safety factor	$\text{A}^2\text{s}\cdot 10^3$	146	$T_j=T_{j\text{ max}}$	180° half-sine wave; $t_p=10\text{ ms}$; $V_R=0.6V_{\text{RRM}}$
BLOCKING					
V_{RRM}	Repetitive peak reverse voltages	V	1100–2000	$t_p=10\text{ ms}$	
V_R	Reverse continuous voltages	V	$0.6\cdot V_{\text{RRM}}$	$T_j=T_{j\text{ max}}$;	
THERMAL					
T_{stg}	Storage temperature	$^{\circ}\text{C}$	−40–160		
T_j	Operating junction temperature	$^{\circ}\text{C}$	−60 –150		
MECHANICAL					
F	Mounting force	kN	3.3 – 5.5		

CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V _{FM}	Peak forward voltage, max	V	2.40	T _j =25 °C; I _{TM} =600A, F=5.0kN	
V _{F(TO)}	Forward threshold voltage, max	V	1.48	T _j =T _{j max} ;	
r _T	Forward slope resistance, max	mΩ	0.65		
BLOCKING					
I _{RRM}	Repetitive peak reverse current, max	mA	20	T _j =T _{j max} ; V _R =V _{RRM}	
SWITCHING					
Q _{rr}	Total recovered charge, max	μC	70	I _{TM} =1000A, t _p =2000μs, -di/dt=60A/μs, V _R =50V	
t _{rr}	Reverse recovery time ¹⁾ , max	μs	2.00		
THERMAL					
R _{thjc}	Thermal resistance, junction to case, max	°C/W	0.0800	Clamping force 5.0kN	Double side cooled
R _{thck}	Thermal resistance, case to heatsink, max	°C/W	0.0200	Clamping force 5.0kN	Double side cooled
MECHANICAL					
w	Weight, max	g	60		

OVERALL DIMENSIONS



ZT26

All dimensions in millimeters