



High-end Power Semiconductor Manufacturer

ZP13500 -WELDING DIODE**200-400 V_{DRM}****WELDING DIODE****Features:**

- All diffused structure
- High current density
- Very low forward voltage drop
- Ceramic housing hermetic package
- Ultra-low thermal resistance

**ELECTRICAL CHARACTERISTICS AND RATINGS****Reverse Blocking**

Device Type	V _{RRM} (1)	V _{RSM} (1)
ZP13500 -02	200	300
ZP13500 -04	400	450


V_{RRM} = Repetitive peak reverse voltageV_{RSM} = Non repetitive peak reverse voltage (2)

Repetitive peak reverse leakage current	I _{RRM}	10 mA 75 mA (3)
---	------------------	--------------------

Notes:

All ratings are specified for T_j=25 °C, unless otherwise stated(1) Sine half wave, f=50Hz, T_j = -40 to +180°C.(2) Sine half wave, Pulse width 10 msec. T_j = -40 to +180°C.(3) Maximum value for T_j = 180 °C.

(4) See parameter definition below :



REVERSE RECOVERY CHARACTERISTIC

Conducting - on state

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Average forward current	I _{F(AV)}		13500		A	Sinewave 180°, T _c =85°C
RMS forward current	I _{FRMS}		21200		A	
Peak one cycle surge (non repetitive) current	I _{FSM}		85000		A	Pulse width 10 msec, sinusoidal wave-shape, 180° conduction, T _j = 180 °C
I square t	I ² t		36100		KA ² s	Pulse width 10 msec, sinusoidal wave-shape, T _j = 180 °C
Peak forward voltage	V _{FM}		0.97		V	I _{FM} = 5000A; 25 °C
Threshold voltage	V _{TO}		0.76		V	T _j = 180 °C
Slope resistance	r _T		0.021		mΩ	T _j = 180 °C
Reverse Recovery Current (4)	I _{RM(REC)}				A	I _{FM} = 1000 A; diF/dt = 10 A/μs; T _j max
Reverse Recovery Charge (4)	Q _{rr}				μC	I _{FM} = 1000 A; diF/dt = 10 A/μs; T _j max
Reverse Recovery Time (4)	t _{rr}				μs	I _{FM} = 1000 A; diF/dt = 10 A/μs; T _j max

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Operating temperature	T_j	-40	+180		°C	
Storage temperature	T_{stg}	-40	+180		°C	
Thermal resistance - junction to case	$R_{\Theta(j-c)}$		0.0039		°C/W	Double sided cooled
Thermal resistance - junction to case	$R_{\Theta(j-c)}$		0.026		°C/W	Single sided cooled
Creepage distance	D_s		2		mm	
Air breakdown distance	D_a		2		mm	
Mounting force	F	35	40	35	kN	
Weight	W			140	g	

* Mounting surfaces smooth, flat and greaseless

CASE OUTLINE AND DIMENSIONS

